TO: EPSON 愛用者

FROM: EPSON 客服中心

主題敘述: 雷射複合機 Epson WorkForce AL-MX300DNF 使用 IE 瀏覽器每次進入印表機 WEB 設定網頁,都會有警告訊息,如何排除

※當使用 IE 瀏覽器時,輸入印表機 IP 位址,瀏覽器都會出現警告訊息,可依下面操作 方式排除。

← ④ https://192.168.6 ♀ ▼ ♂ × ◎ 憑證錯誤: 瀏覽已封鎖 ×	<b>↑</b> ★ ¤
此網站的安全性憑證有問題。	*
此網站出示的安全性憑證並非由信任的憑證授權單位所發行。 此網站出示的安全性憑證是為其他網站的位址所發行的。	
安全性憑證問題可能表示其他人可能正在嘗試欺瞞您,或是擴戰您傳送到該伺服器的任何資料。	
我們建議您闡閉此網頁,而且不要繼續瀏覽此網站。	
❷ 按這裡關閉此網頁。	
😵 繼續瀏覽此網站 (不建議)。	
● 其他資訊	
	*

步驟1、點選「繼續瀏覽此網站(不建議)」選項。

步驟 2、之後畫面會進入印表機的 EpsonNet Config 的 WEB 設定畫面,點選「Network Administrator(網路管理員)」。

🧲 🕣 🥖 🖊 192 ,O - 🕉 🗟 C	🗙 <i>i EpsonNet Config</i>	×	<b>↑</b> ★ ☆
EpsonNet Config	Margan and		EPSON
Home Favorite			Help
Network System			
Administrator			
Information		网络安位亚	
Printer		● 「「「「「「「「」」」」 「「「「」」」 「「」」 「「」」 「「」」 「	
System		44 四 言品語 -000 000+ 文件大小 品語 濃淡度	
<u>System Information</u>			
<u>Machine Status</u>		Error Information	
Language		Sleep	
Common Settings			-
Printer Settings			=
Scan Settings			_
Fax Settings	Continue Warmup		
Address Settings			
Fax No.	System Information		
Admin Settings	Printer Model Name	AL-MX300	
Network	Main Version	00.22	
Network	Fax Version	00.16	
	MCU Version	0002030000	
Configuration	Serial No	TRD2000002	
Printer	Memory [MB]	1024	
	MAC Address	AC18267B0039	
	IP Address	192.168.6.134	•

步驟 3、「Security(安全性)」選單,點選「SSL/TLS (安全通訊協定/傳輸層安全協議)」。

(←) → @	192 🔎 👻 🔯 🖉 🖉 EpsonNet Cor	nfig ×	<b>n</b> ★ ₩
EpsonNet			EPSON
Home Favorite			Help
Network Administrator	Network Administrator - Network TCP/IP - IPv4 Address		2
Network TCP/IP	Method for Specifying IP Address	Manual 👻	
IPv4 Address     IPv6 Address     Date DDate	Setting Automatic Private IP Addressing (APIPA)	Diseble V	
• <u>DINSIDDINS</u> <u>WSD</u> ULTD	Setting PING	Disable -	
IPP/IPPS	IP Address(Manual)	192.168.0.134	
Bonjour	Subnet Mask(Manual)	255.255.255.0	
MS Network	Default Gateway(Manual)	192.168.6.254	
<u>SNMP</u> <u>Time Server</u>		Transmit	
Printing/Scan Protocol			
Email Server			
LDAP			
Security			
IPsec/Access Control			
IEEES02.1X			
Authentication -			
< <u> </u> ►			

步驟 4、「Automatic Redirect HTTP to HTTPS (安全通訊協定/傳輸層安全協議)」,將 Enable(啟用),改為 Disable(不啟用)。

			- • ×
< -> €	192 🔎 - 🗴 🗟 C 🗙 🥥 EpsonNet Co	onfig ×	<b>↑</b> ★ ☆
EpsonNet Config			EPSON
Home Favorite			Help
Network Administrator	Network Administrator - Security SSL/TLS		2
TCP/IP WIED	Server Certificate	Self-Signed Certificate 💌	
LLTD	Encryption Strength	Medium(RC4-128,3DES-168,AES-128/256) -	
IPP/IPPS	Automatic Redirect HTTP to HTTPS	Enable 🔻	
<u>UPnP</u>		Transmit	
Bonjour MC Material	<u></u>		
<u>SNMP</u> <u>Time Server</u> <u>Printing/Scan</u>	Network Administrator - Security Authentication - Certificate List	Open Details	
Email Server	Self-Signed Certificate		
LDAP	Status	Used	
Security	Subject	172.21.23.56	
IPsec/Access Control			
<u>SSL/TLS</u>	CA-Signed Certificate1		
IEEE802.1X	Status	No Certificate	Delete
Security Setup	Subject		
	CA-Signed Certificate2		
Option -	Status	No Certificate	Delata
< <u> </u>	Subject		- Deleie -



步驟 5、點選「Transmit(傳送)」, 關閉瀏覽器(按右上角「X」)即完成設定。

<->€	192 ♀ × ☎ ♂ × 遵 EpsonNet Co	onfig ×	<b>↑</b> ★ ¤
EpsonNet Config			EPSON
Home Favorite Network Administrator Network	Network Administrator - Security SSL/TLS		Help
TCP/IP WSD LLTD IPP/IPPS UPnP Boniour MS Network	Server Certificate Encryption Strength Automatic Redirect HTTP to HTTPS	Self-Signed Certificate  Medium(RC4-128,3DES-168,AES-128/256)  Clicable  Transmit	
<u>SNMP</u> <u>Time Server</u> <u>Printing/Scan</u> <u>Protocol</u> Email Server	Network Administrator - Security Authentication - Certificate List	Open Details	
LDAP Security IPsec/Access Control	Status Subject	Used 172.21.23.56	Create
SSL/TLS IEEE802.1X Authentication Security Setup	CA-Signed Certificate1 Status Subject	No Certificate	Delete
Option -	CA-Signed Certificate2 Status Subject	No Certificate	Delete